


Front Loaders
Roll-Off Hoists
Hook-Lifts
Trailers
Luggers
Dump Box
Compactors
Refuse Containers

Universal

Lugger Truck



Designed to provide the maximum in lifting capacity

Universal Handling Equipment's

Universal Lugger Truck

Comparisons

120-H-40 120-H-50 **Gross Lifting Capacity** 40,000 lbs 50,000 lbs Standard Container Size 6 - 22 cu. yds. 6 - 22 cu. yds. Hydraulic Pump Capacity 46 gpm @1,200 rpm 46 gpm @1,200 rpm **Normal Operating Pressure** 2,000 PSI max. 2,200 PSI max. 8 3/4" Diameter x 70" Stroke **Hoist Cylinders** 8 3/4" Diameter x 70" Stroke

Jackleg StabilizersHydraulicHydraulicCycle Time - Down47 Seconds47 SecondsCycle Time - Up42 Seconds42 SecondsMinimum Cab To Tandem Axle132" CA132" CA

In addition to the above, all truck chassis should meet counterbalance requirements to assure operation at full capacity - for this, front and rear curb weights are required. We recommend confirming chassis specifications prior to purchase of a chassis.

Special Features

- Easy access to the hydraulic system, oil strainer and visual tank gauge. Gate valve for instant shut off of hydraulic oil from the tank.
- The hydraulic dump pins are rigidly designed to withstand unloading stresses, so that no important moving part comes into contact with the J-Hooks during dumping operation.

Standard Features

- Both Universal Lugger models are hydraulicaly operated and controlled by means of in-cab lever controls. The cylinders are double-acting, self bleeding type with screw type gland nut. Fittings, hoses and pipes are of high-pressure type. The pump is a heavy duty, high efficiency, bi-rotational type, rated 39 gpm @ 1,000 rpm and 2,000 PSI @ 1,200 rpm.
- The frame and body are of heavy duty construction with 10" channel frame understructure, 1/4" high tensile steel floor plates and 1/2" high tensile steel side plates. Rigid jacklegs are provided at the rear to steady the unit when lifting loaded containers.

Options

- Chassis Mounted Tarp Box
- Auxillary Lift Axles
- Hydraulic Tarper System
- Pintle Hook
- Headache Rack
- Wear Strips



Jack Leg



Hydraulic Tank



xterior Controls



4024 Charles Street Red Deer County Alberta, T4S 2B3 Canada

Alberta, T4S 2B3 Michigan, 48867 Canada U.S.A. Sales: 403.346.1233 Sales: 989.725.16

U.S.A. Sales: 989.725.1640

1650 Industrial Drive

Owosso



8120 Lawson Road, Unit #2 Milton Ontario, L9T 5C4 Canada 905.662.3318

universalhandling.com

Western Canada Toll Free: 1.877.UHE.6163 (1.877.843.6163) Eastern Canada Toll Free: 1.877.UHE.1122 (1.877.843.1122)