



616-863-9155 | equipment@amplirollusa.com | amplirollusa.com

60,000-
65,000
POUNDS



WHY BUY A HOOKLIFT?

Do you have trucks that are not always being used?

Do you have a difficult time finding quality drivers?

Is there a piece of equipment you could use, but can't justify adding another truck?

It's Multi-tasking for your truck.
The possibilities are Infinite.

DELIVER | LOAD | DUMP

The **Ampliroll Hooklift** was invented in 1969. Our process of laser cutting and robotic welding enables us to provide you with a complete line of hooklifts, that eliminate the use of SHIMS and WEAR PADS.



FEATURES:

- **Sliding Jib** gives you greater range of body lengths and optimal weight distribution.
- **Twin Pivot** allows you to dump a uniform pile of material.
- **Dual Cylinders** gives greater stability while dumping and loading.
- **Safely operated** from the drivers seat.
- **Dock Level** loading and unloading
- **Double your payload** by pulling another body on a trailer.
- **Maneuverable** to operate, the container can be loaded within a 60 degree arc.
- **Spot** the container exactly where you want it, by pushing it into place with no damage.
- **Quickly loads** a body in less than one minute.
- **Investment** that will outlast your truck, Amplirolls® will last over 25 years.
- **Meets** all highway safety standards.

AMPR 160-185-17**AL 160/2000-22****LIFTING CAPACITY**
(including container)

60,000 lbs.

65,000 lbs.

SHIPPING WEIGHT

5148 lbs.

7030 lbs.

DUMP ANGLE

56°

57°

CAB TO TRUNNION*

138" - 168"

186" - 200"

OVER ALL LENGTH

From Hook**

194"

233"

BODY LENGTH

12' - 19'

16' - 24'

HOOK HEIGHT**Standard**

61 3/4"

STEEL: SPECIAL ALLOY**ASTM A 514**

in jib, central arm and tilting frame

ASTM A 572

grade 60 type 2 subframe

HYDRAULIC SPECIFICATIONS:**Pump**Axial piston, 5,700 psi, 23 GPM @ 1,200
Standard - DIN Shaft or Optional SAE 7/8th
Shaft**Controls**

Low pressure hydraulic, cable or air in cab

Reservoir

20 gallons

Filter10 micron, return line with replaceable
cartridge**Maximum operating pressure**

4,800 psi

Hoses, tubes & fittings

all JIC/SAE specifications

SAFETY DEVICES:**Safety valve**prevents jib operation during dump
mode**Counter-balance valve**

to hold cylinder if hose breaks

Automatic locking device

for dump mode

Slide through container locks**TRUCK REQUIREMENTS:****GVWR**50,000 to
80,000 lbs**Front Axle****Capacity**
16,000 to
20,000 lbs**Rear Axles****Capacity**40,000 to
60,000 lbs**Minimum RBM**2,750,000 in.
lbs**NOTICE:**

Longer containers may not comply with I.C.C. bumper regulations and can effect dump angle.

*Need to confirm CA or CT with factory or local dealer for proper installation.

**Some subframes are longer, check with local dealer.



4750 14 Mile Road NE | Rockford, MI 49341

Phone: 616-863-9155

Fax: 616-863-9177

Toll Free: 866-822-3580

equipment@amplirollusa.com

amplirollusa.com

Distributed by:

